


REDUCING PLUG MALE BSPP - FIXED FEMALE BSPP (1)

SHORT REDUCTION - MALE GAS CYLINDRICAL SV 60° - FIXED
FEMALE GAS CYLINDRICAL



Code	Thread		Dimensions			Pressure	
	F1	F2	H1 mm	L1 mm	L mm	Bar	Psi
BRB4-2	1/4"	1/8"	19	11	18	350	5075
BRB6-2	3/8"	1/8"	22	12.5	21.5	350	5075
BRB6-4	3/8"	1/4"	22	12.5	21.5	350	5075
BRB8-2	1/2"	1/8"	27	14	24	315	4568
BRB8-4	1/2"	1/4"	27	14	24	315	4568
BRB8-6	1/2"	3/8"	27	14	24	315	4568
BRB12-4	3/4"	1/4"	32	16	27	250	3625
BRB12-6	3/4"	3/8"	32	16	27	250	3625
BRB12-8	3/4"	1/2"	32	16	27	250	3625
BRB16-4	1"	1/4"	41	18	32	200	2900
BRB16-6	1"	3/8"	41	18	32.5	200	2900
BRB16-8	1"	1/2"	41	18	31.5	200	2900
BRB16-12	1"	3/4"	41	18	32	200	2900

The information gathered in this technical documentation (Catalogue) has an informative character and can be modified without previous notice. INDIA STEEL COMPANY will not accept any type of responsibility resulting from an inappropriate use of the product, except the ones related to manufacturing defects. www.hydromechqatar.com

MAKE IN INDIA